

## Housings for filter cartridges

### STAINLESS STEEL SS 316 L HOUSINGS

# FILTERBLACK FBK-02

[Link to product's PDF drawing](#) 

#### TECHNICAL FEATURES:

Type	FILTERBLACK FBK-02
Material	AISI 316 L
In/Out	DN 80 FLANGE EN1092

#### DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50 C°

#### CARTRIDGES

N° cartridges	2
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



#### APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridge s	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	€/each
FBK316LBL0220M	FILTERBLACK FBK-02 2x20"	Ceramic blasted	20"	DN 80 FLANGE EN1092	1.000	BL	1	-

# Housings for filter cartridges

## STAINLESS STEEL SS 316 L HOUSINGS

### FILTERBLACK FBK-02

#### HOUSINGS CODE LIST

Model	Material	Cartridges end cap typ	Cartridges n°	Cartridges height	Specs and finishing
FBK	AISI 316 L 316L	BL BL	2 02	20" 20	Ceramic blasted M



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure*



**European Community members only.**

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

**Design code:** ASME VIII