

REVERSE OSMOSIS ANTISCALANT

Vitec™ 5100

Antiscalant / Dispersant

APPLICATIONS

Vitec™ 5100 is a liquid antiscalant and dispersant targeted at preventing scale precipitation in larger systems and is particularly cost effective in seawater and municipal reverse osmosis (RO) applications. This full spectrum antiscalant is also very effective in high iron and organic waters.

INJECTING

Best results are achieved when Vitec 5100 is injected downstream of multimedia filters and upstream of cartridge filters.

DOSING

A typical Vitec 5100 dose ranges from 0.5 to 2.0 mg/l. A site-specific dose can be determined using the Avista™ Advisor™Ci software program.

DILUTION

Vitec 5100 is formulated to be injected neat. However, if dilution is required, use deionized water or RO permeate. If neither of these is available, soft water may be substituted. The dilution for Vitec 5100 should not result in a solution strength of less than 10%. This guideline protects the effectiveness of the internal bacteriostat, which inhibits bacterial growth in the product packaging and feed tank.

CHEMICAL AND PHYSICAL PROPERTIES

CHARACTERISTICS	DATA
Appearance	Clear to amber liquid
pH (2% solution)	5.0 – 6.5
Specific gravity (@25°C)	1.05 – 1.15

PERFORMANCE BENEFITS

- Powerful against these and other types of scale:

Calcium carbonate	CaCO ₃
Calcium sulfate	CaSO ₄
Barium sulfate	BaSO ₄
Silica	SiO ₂

- Antiscalant targeted at preventing scale precipitation in larger seawater and municipal RO applications.
- Full spectrum antiscalant that can prevent several types of scales.
- Very effective in high iron and organic waters.
- Compatible with membranes from all major manufacturers.
- Compatible with Avista coagulants.
- Effective in a wide variety of feedwater pH ranges.

PACKAGING

Standard regional pack sizes are listed below. Information on bulk delivery options is available on request.

PACKAGING FORMAT	EMEA
IBC	1100 kg
Drum	230 kg
Pail/Bag	–
Jerry Can	20 kg

Please consult your sales representative for further technical or logistical details, and always review the SDS before use to ensure suitable safety precautions are followed.

Please consult your sales and technical consultant.

Kurita Europe GmbH
Theodor-Heuss-Anlage 2
DE-68165 Mannheim
☎ Telephone: +49 621 1218 3000

The information contained herein reflects our current level of technical knowledge and experience. It does not constitute a legal warranty of particular characteristics or of fitness for a specific purpose and, due to the abundance of possible influences, does not exempt the user from making its own examinations and taking appropriate precautionary measures. It shall be the responsibility of the recipient of our products to respect any intellectual property rights and comply with any laws or other provisions.
© 2022 Kurita Water Industries. (202005)



www.kurita.eu
kuritaeurope@kurita-water.com

