


Housings for filter cartridges STAINLESS STEEL SS 316 L HOUSINGS

FILTRO FILTERBLACK FBKE-BL-3RS

[Link to PDF product's drawing](#)

 everblue.it/CadDrawings/F20170314152741457FBKE3RS316BL0620M

FEATURES



Model	FILTRO FILTERBLACK FBKE-BL-3RS
Material	SS 316 L
In/Out	DN 125 FLANGE EN1092

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	80°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	6
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FBKE3RS316LBL0620M	FILTRO FILTERBLACK FBKE-BL-3RS 6x20"	Ceramic blasted	20"	DN 125 FLANGE EN1092	2333	BL	1	

Housings for filter cartridges STAINLESS STEEL SS 316 L HOUSINGS

FILTRO FILTERBLACK FBKE-BL-3RS

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FBKE3RS	AISI 316 L 316L	BL BL	6 06	20" 20	Ceramic blasted M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4