


Housings for filter cartridges STAINLESS STEEL SS 316 L HOUSINGS

FILTRO FILTERBLACK FBKE-BL-2RS

[Link to PDF product's drawing](#)

 everblue.it/CadDrawings/F20170314152723560FBKE2RS316BL0420M

FEATURES



Model	FILTRO FILTERBLACK FBKE-BL-2RS
Material	SS 316 L
In/Out	DN 100 FLANGE EN1092

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	80°C
Life test	1.000 cycles from 0 to 10 bar

CARTRIDGES

N° cartridges	4
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FBKE2RS316LBL0420M	FILTRO FILTERBLACK FBKE-BL-2RS 4x20"	Ceramic blasted	20"	DN 100 FLANGE EN1092	1500	BL	1	

Housings for filter cartridges STAINLESS STEEL SS 316 L HOUSINGS

FILTRO FILTERBLACK FBKE-BL-2RS

HOUSINGS CODE LIST

Model		Material		Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FBKE2RS		AISI 316 L	316L	BL	BL	4	04	20"	20	Ceramic blasted	M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014.

These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

Design code: ASME VIII