

## Housings for filter cartridges

### FIBERGLASS HOUSINGS

# FILTRO FILTERBLANC-BL-02

[Link to PDF product's drawing](#)

 [www.everblue.it/CadDrawings/F20180628114758267FBCFRPBL0220WH](http://www.everblue.it/CadDrawings/F20180628114758267FBCFRPBL0220WH)

#### FEATURES



Model	FILTRO FILTERBLANC-BL-02
Material	FRP
In/Out	DN 80 FLANGE DN8063 PN16

#### DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50°C
Life test	1.000 cycles from 0 to 10 bar

#### CARTRIDGES

N° cartridges	2
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



#### APPLICATIONS

Water  
Sea water

Code	Description	Specs, colors and particular finishing	Cartridges height	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	-
FBCFRPBL0220WH	FILTRO FILTERBLANC-BL-02 2x20"	White	20"	DN 80 FLANGE DN8063 PN16	1000	BL	1	

## Housings for filter cartridges FIBERGLASS HOUSINGS

# FILTRO FILTERBLANC-BL-02

### HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FBC	FRP (Fiberglass)	BL BL	2 02	20" 20	White WH



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure*



#### European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13.1

**Design code:** BS EN 13923 2005